

# **CRIS AZUL**



# BASIC TREATMENT FOR CRYSTALLISATION OF MARBLE FLOOR

- It quickly eliminates the porosity of calcareous floors
- Perfect to prepare the final crystallisation by Cris
- Suitable also for external floors

Highly concentrated formula suitable for calcareous surfaces (marble, travertine, Jura limestone and all calcareous floors), it quickly eliminates the porosity of calcareous floors.

## ⑦ HOW TO USE

By low speed single disc machine (max 150 rpm, minimum 45 kgs. weight, 00 steel-wool pad equipped). For best result: strip the floor with a sripper of Sutter Professional range. Let the floor dry. Spray a little amount of Cris Azul and treat the floor until it becomes highly glossy (4-5 min. / sq.m.). Crystallise the floor using Cris.



# **DILUTION**

Ready to use.

#### FEATURES

Product yields (m<sup>2</sup>/lt):

Operation category	Conc.%	Product yield (m <sup>2</sup> /lt)	Notes
MARBLE CRYSTALLIZING	100%	80 - 100	Single disk machine equipped with extra weight and steel wool pad

Volume (It) of pure product diluted according to suggested dilutions.

SUTTER INDUSTRIES S.p.A Località Leigozze 1, 15060 Borghetto Borbera - Tel. +39 0143 631.1 www.sutterprofessional.com- info@sutterprofessional.com





Rev. 11/03/2024



# **CRIS AZUL**

#### R TECHNICAL DATA

ASPECT: Opaque liquid COLOR: Blue PERFUME: Floral

PH	PH Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
1,5 ± 0,5	31 ± 2	1,160			

### () WARNINGS

Harmful if swallowed. Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects. Wear eye protection. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Contents MAGNESIUMHEXAFLUOROSILICATE.



#### NOTES 🕼

Keep away from freezing. Do not apply at temperatures below 10°C. Before use, please always refer to the Technical Data Sheet and the Safety Data Sheet, with the exposure scenario, of the product. Use the PPE specified in the Safety Data Sheet. Sutter Professional cannot be considered liable for any damage due to improper product use. **Only for professional use. Safety data sheet available on request.** 

## 

Code	Size	Quantity	Pallet
5439	Kg 5	4	9x4=36

