

# **IF 110**



## SOLVENT-BASED WATER AND OIL-REPELLENT IMPREGNATOR

- High waterproofing power
- It does not alter natural colours or the appearance
- Ideal for terracotta and natural stones

Specific formulation for the water and oil-repellent treatment of terracotta and natural stone floors. It offers excellent waterproofing without altering the appearance and prevents the resurfacing of salt efflorescence.

### ? HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, and after descaling using a special acid (for terracotta floors), apply one or two coats of IF 110 using the special wax applicator. Leave to dry approximately 30 - 60 min. between one coat and the next. To get a glossy finish, afterwards apply the product FL 201 NEUTRO.







#### **IF 110**

#### **DILUTION**

Ready to use.

#### **FEATURES**

Product yields (m<sup>2</sup>/lt):

Operation category	Conc.%	Product yield (m²/lt)	Notes
STONE & CONCRETE TREATING	1()()%		1 coat

Volume (It) of pure product diluted according to suggested dilutions.

## **A TECHNICAL DATA**

ASPECT: Clear liquid COLOR: Colorless PERFUME: Technical

**COV:** 94,00%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
0.852				6,3 ± 0,6	

#### (!) WARNINGS

Flammable liquid and vapour. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. IF SWALLOWED: Immediately call a POISON CENTER or a doctor. Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. In case of fire, use a dry powder fire extinguisher to extinguish. Store in a well-ventilated place. Keep cool. Contains HYDROCARBONS, C9-11, ALKANES, 1-METHOXY-2-PROPANOL.







WARNING



DANGER





#### IF 110

## **№** NOTES

Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product.

Before use, please always refer to the Technical Data Sheet and the Safety Data Sheet, with the exposure scenario, of the product. Use the PPE specified in the Safety Data Sheet.

Sutter Professional cannot be considered liable for any damages due to an improper product use.

Only for professional use. Safety data sheet available on request.

# **PACKAGING**

Code	Size	Quantity	Pallet
3949	L5	4	8x4=32

